

Таблица 5. 11. Переносные свойства фреона 22 на линии насыщения

T	μ'	μ''	λ'	λ''
233.15	3.387E-4	1.019 E-5	1.150E-1	6.66E-3
243.15	2.945 E-4	1.066 E-5	1.102E-1	7.37 E-3
253.15	2.604 E-4	1.115 E-5	1.055E-1	8.12 E-3
263.15	2.314 E-4	1.166 E-5	1.008E-1	8.91 E-3
273.15	2.080 E-4	1.221 E-5	9.57E-2	9.75 E-3
283.15	1.884 E-4	1.274 E-5	9.12 E-2	1.065E-2
293.15	1.700 E-4	1.337 E-5	8.66 E-2	1.161 E-2
303.15	1.520 E-4	1.404 E-5	8.24 E-2	1.266 E-2
313.15	1.342 E-4	1.483 E-5	7.84 E-2	1.382 E-2
323.15	1.184 E-4	1.578 E-5	7.42 E-2	1.513 E-2
333.15	1.072 E-4	1.699 E-5	7.03 E-2	1.666 E-2
343.15	9.47E-5	1.863 E-5	6.58 E-2	1.852 E-2
353.15	8.09 E-5	2.110 E-5	6.09 E-2	2.10 E-2
363.15	6.36 E-5	2.540 E-5	5.33 E-2	2.50 E-2
365.15	5.88 E-5	2.680 E-5	5.10 E-2	2.63 E-2