

Таблица 5. 18. Переносные свойства фреона 32 на линии насыщения

T	μ'	μ''	λ'	λ''
203.15		7.89E-6	1.65E-1	7.90E-3
213.15		8.28 E-6	1.56E-1	8.36E-3
223.15		8.68 E-6	1.48E-1	8.85E-3
233.15	2.351E-4	9.08 E-6	1.40E-1	9.38E-3
243.15	2.122E-4	9.49 E-6	1.32E-1	9.96E-3
253.15	1.911E-4	9.91 E-6	1.25 E-1	1.06 E-2
263.15	1.716E-4	1.03 E-5	1.19 E-1	1.13 E-2
273.15	1.530E-4	1.12 E-5	1.12 E-1	1.21 E-2
283.15	1.362E-4	1.17 E-5	1.06 E-1	1.29 E-2
293.15	1.209E-4	1.22 E-5	9.91E-2	1.39 E-2
303.15	1.065E-4	1.29 E-5	9.26 E-2	1.51 E-2
313.15	9.35E-5	1.36 E-5	8.60 E-2	1.65 E-2
323.15	8.27E-5	1.44 E-5	7.90 E-2	1.82 E-2
333.15	7.40E-5	1.57 E-5	7.66 E-2	2.53 E-2
343.15		1.79 E-5	7.51 E-2	4.03E-2