

Таблица 5. 20. Переносные свойства фреона 125 на линии насыщения

T	μ'	μ''	λ'	λ''
173.15		7.41E-6		
183.15		7.82 E-6		
193.15		8.25 E-6		
203.15		8.67 E-6		
213.15		9.11 E-6	9.70 E-2	8.52 E-3
223.15		9.55 E-6	9.29 E-2	9.15 E-3
233.15	3.383 E-4	1.00 E-5	8.89 E-2	9.80 E-3
243.15	2.902 E-4	1.05 E-5	8.49 E-2	1.05 E-2
253.15	2.511 E-4	1.10 E-5	8.10 E-2	1.12 E-2
263.15	2.189 E-4	1.16 E-5	7.72 E-2	1.21 E-2
273.15	1.915 E-4	1.22 E-5	7.32 E-2	1.30 E-2
283.15	1.683 E-4	1.29 E-5	6.93 E-2	1.41 E-2
293.15	1.477 E-4	1.37 E-5	6.54 E-2	1.55 E-2
303.15	1.295 E-4	1.45 E-5	6.12 E-2	1.72 E-2
313.15	1.155 E-4	1.56 E-5	5.68 E-2	1.94 E-2
323.15	1.089 E-4	1.71 E-5	5.18 E-2	2.21 E-2
333.15		2.00 E-5	4.53 E-2	2.58 E-2