

**Таблица 7.4. Переносные свойства диоксида углерода на линии насыщения.**

$T$	$\mu'$	$\mu''$	$\lambda'$	$\lambda''$
270	1,054 E-4	1,471 E-5	1,146 E-1	1,964 E-2
272	1,020 E-4	1,492 E-5	1,126 E-1	2,019 E-2
274	9,867 E-5	1,514 E-5	1,105 E-1	2,078 E-2
276	9,535 E-5	1,538 E-5	1,084 E-1	2,141 E-2
278	9,207 E-5	1,563 E-5	1,063 E-1	2,210 E-2
280	8,882 E-5	1,590 E-5	1,042 E-1	2,284 E-2
282	8,560 E-5	1,620 E-5	1,021 E-1	2,365 E-2
284	8,236 E-5	1,652 E-5	9,997 E-2	2,455 E-2
286	7,915 E-5	1,688 E-5	9,784 E-2	2,554 E-2
288	7,589 E-5	1,727 E-5	9,568 E-2	2,665 E-2
290	7,260 E-5	1,772 E-5	9,349 E-2	2,791 E-2
292	6,924 E-5	1,823 E-5	9,124 E-2	2,935 E-2
294	6,576 E-5	1,883 E-5	8,891 E-2	3,104 E-2
296	6,213 E-5	1,956 E-5	8,645 E-2	3,305 E-2
298	5,827 E-5	2,049 E-5	8,379 E-2	3,555 E-2
300	5,400 E-5	2,173 E-5	8,077 E-2	3,883 E-2
301	5,163 E-5	2,257 E-5	7,904 E-2	4,094 E-2
302	4,898 E-5	2,367 E-5	7,704 E-2	4,360 E-2
303	4,591 E-5	2,527 E-5	7,460 E-2	4,725 E-2
304	4,198 E-5		7,121 E-2	